



FLEX 10X5 VERTICAL DOMED



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP65
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
STANDARDS	EN/AS/NZS 60598-2-1, 62031, 62471
WARRANTY	5 Years

MONO CCT

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	>30 mm
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver
ADHESIVE BACKING⁽¹⁾	If backing is used, the flex will not fit into the aluminium profile accessory

	LED SPECIFICATION			LUMEN PACKAGE lm/m						
	Wattage	Max. Length	Cut Interval	1800K	2400K	2700K	3000K	3500K	4000K	6000K
SF05	5 W/m	12 m	25 mm	338	442	484	520	530	546	538
SF10	10 W/m	8 m	25 mm	672	880	962	1036	1056	1088	1072
SF15	15 W/m	6 m	25 mm	888	1160	1268	1364	1392	1432	1412

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	ADHESIVE BACKING	LENGTH
63S1005VD Neon Flex 10x5 VD	1 White	C18 1800K C24 2400K C27 2700K C30 3000K C35 3500K C40 4000K C60 6000K	SF05 5 W/m (12m max. V24) SF10 10 W/m (8m max. V24) SF15 15 W/m (6m max. V24)	E End	5 IP65	003 0.3m 010 1m 030 3m 050 5m 100 10m	A 3M Backing Included ⁽¹⁾	.XXXX Length in mm
63S1005VD	1			E	5		<i>OPTIONAL</i>	

ACCESSORIES

TYPE	Aluminium push in profile
MOUNTING	Surface mount

ORDERING INFORMATION

MODEL	FINISH	LENGTH
63S1005X	5PP Aluminium	0020 20mm 1000 1000mm 2000 2000mm
63S1005X	5PP	

