

## Type 3528

## LED Tape



### Specification

<b>Length</b>	5m Reel (custom lengths to order)
<b>IP Rating</b>	IP20, IP65, IP68
<b>LED</b>	Type 3528 - 24V
<b>Connector</b>	Wire tails

### Specification

LED Type	222	255	244	266	288	278	299	282	285	284	286
<b>LEDs</b>	60	96	120	180	240	240	360	240	240	240	240
<b>Rows</b>	1	1	1	1	1	2	3	1	1	1	1
<b>Power/m</b>	4.8W	7.68W	9.6W	14.4W	19.2W	19.2W	28.8W	4.8W	7.68W	9.6W	14.4W
<b>Output/m</b>	418lm	668lm	835lm	1253lm	1670lm	1670lm	2506lm	418lm	668lm	835lm	1253lm
<b>Cut point (mm)</b>	100mm	62.5mm	50mm	33.3mm	25mm	50mm	50mm	25mm	25mm	25mm	25mm

### Ordering Information example 6412.A27288

Model	LED CCT	LED Type
6412. IP20	<b>CRI &lt; 80Ra</b>	222 4.8W - 60/m - 418lm
6416. IP65	A60 6000°K	255 7.68W - 96/m - 668lm
6418. IP68	<b>CRI &gt; 80Ra</b>	244 9.6W - 120/m - 835lm
	B24 2400°K	266 14.4W - 180/m - 1253lm
	B27 2700°K	288 19.2W - 240/m - 1670lm
	B30 3000°K	278 19.2W - 2x120/m - 1670lm
	B40 4000°K	299 28.8W - 3x120/m - 2506lm
	<b>CRI &gt; 90Ra</b>	<b>HD (High Density)</b>
	C27 2700°K	282 4.8W HD - 240/m - 418lm
	C30 3000°K	285 7.68W HD - 240/m - 668lm
		284 9.6W HD - 240/m - 835lm
		286 14.4W HD - 240/m - 1253lm

(i) Typical lumen output subject to selected CCT.